

IA-1007

4-ch, 5Amp
Relay module
Discrete Control

IA Intelligent Appliance
For Smart Solutions...



Features

- 4-ch SPDT Power Relay
- +3V to +30VDC Control Voltage
- 12V and 24V Version, Supply Voltage
- Status Indicator Leds
- Contacts Protection Suppressors
- DIN-Rail mounting ready

Introduction

Intelligent-Appliance IA-1007 Discrete Relay Module was designed for a simple conversion of digital output into a dual pole 'Dry-Contact' output with a contact rating of 5Amp.

The IA-1007 Discrete Relay Module includes 4 SPDT Relays, Led status indicators and voltage suppressors across their contacts to eliminate EMI/RFI noise while being switched.

Control voltage operation range is +3 to 30VDC at a current of 1mA to 11mA.

Specifications

Relays

Channels	4
Type	SPDT
Current Rating	5Amp @ 30VDC 5Amp @ 120VAC
Control Voltage	3-30 VDC
Control Current	1-11 mA

General

Power Consumption	1.5w
Size	114x56x50mm
Weight	104gr

Ordering information

- IA-1007-12
4-ch Discrete Relay Module,
3-30V Control Voltage,
12VDC Supply Voltage
- IA-1007-24
4-ch Discrete Relay Module,
3-30V Control Voltage,
24VDC Supply Voltage

